

Cod. 10505

Hose reel machines



Explorer

Slow reverse double arm gun for high flow



| | | | | |
|--------------|------------------------|---------------------------|---------------------|------------|
| Net weight | Connection | Size | Nozzle | Angle |
| 11 kg | 6 x 130 mm (M8) | ø 1812 mm x 595 mm | ø 22 ÷ 42 mm | 25° |

Pressure *Presion*

| Nozzle | 3 bar | | 4 bar | | 5 bar | | 6 bar | | 7 bar | | 8 bar | |
|--------------|-------------------|------------------|-------------------|------------------|-------------------|------------------|-------------------|------------------|-------------------|------------------|-------------------|------------------|
| | Flow Caudal l/min | Radius Alcance m | Flow Caudal l/min | Radius Alcance m | Flow Caudal l/min | Radius Alcance m | Flow Caudal l/min | Radius Alcance m | Flow Caudal l/min | Radius Alcance m | Flow Caudal l/min | Radius Alcance m |
| 22 mm | 522 | 40 | 604 | 44 | 676 | 48 | 741 | 52 | - | - | - | - |
| 24 mm | 623 | 41 | 720 | 46 | 806 | 50 | 882 | 54 | - | - | - | - |
| 26 mm | 732 | 43 | 846 | 48 | 946 | 52,5 | 1037 | 56 | - | - | - | - |
| 28 mm | 848 | 46 | 981 | 50,5 | 1096 | 54 | 1202 | 58 | - | - | - | - |
| 30 mm | 974 | 48 | 1127 | 52 | 1260 | 56 | 1381 | 60 | - | - | - | - |
| 32 mm | - | - | 1282 | 54 | 1433 | 58 | 1570 | 62 | 1694 | 66 | - | - |
| 34 mm | - | - | - | - | 1619 | 59 | 1774 | 64 | 1913 | 68 | 2048 | 72 |
| 36 mm | - | - | - | - | 1814 | 61 | 1988 | 66 | 2144 | 70 | 2295 | 74 |
| 38 mm | - | - | - | - | 2022 | 63 | 2216 | 68 | 2390 | 72 | 2558 | 76 |
| 40 mm | - | - | - | - | 2240 | 65 | 2455 | 69 | 2648 | 73 | 2834 | 78 |