

P27 - Overhead sprinklers

ADJUSTABLE PLASTIC SPRINKLER

Applications

- For residential and small public areas, also as hose-end on spike or sled bases

Features

- Adjustable plastic impact sprinkler
- No-splash hammer
- Deflector vane and diffuser allow the control of radius and distribution
- 1/2" male thread
- Trajectory 25°
- Stainless steel pin and spring, effective sand protection
- Colour-coded plastic nozzles
- Spacing between sprinklers: up to 14 meters



Performance table

| NOZZLE colour ø mm | P (bar) | Q (m ³ /h) | D (m) | NOZZLE colour ø mm | P (bar) | Q (m ³ /h) | D (m) |
|-----------------------|------------|--------------------------|----------|---|------------|--------------------------|----------|
| orange 2,8 | 2,0 | 0,45 | 22,0 | blue 3,5 | 1,0 | 0,49 | 20,0 |
| | 3,0 | 0,55 | 23,0 | | 2,0 | 0,66 | 23,0 |
| | 4,0 | 0,63 | 24,0 | | 3,0 | 0,81 | 24,0 |
| red 3,0 | 1,0 | 0,36 | 19,0 | black 4,0 | 1,0 | 0,60 | 21,0 |
| | 2,0 | 0,51 | 23,0 | | 2,0 | 0,85 | 24,0 |
| | 3,0 | 0,63 | 24,0 | | 3,0 | 1,03 | 26,0 |
| green 3,2 | 1,0 | 0,41 | 20,0 | Performance table prepared under laboratory conditions Adjustments apply according to field conditions | | | |
| | 2,0 | 0,57 | 23,0 | | | | |
| | 3,0 | 0,70 | 24,0 | | | | |

MODELO HABITUALMENTE DISPONIVEL EM STOCK

Nova Rocha
SISTEMAS E EQUIPAMENTOS DE REGA

