



SKY

Quality drip tape



07.2015





Ø 16 mm



filtrazione richiesta

filtration required
filtrage recommandé
filtración requerida
требуемый уровень фильтрации

100 micron
150 mesh

Dati tecnici

Technical data / Donnes techniques / Datos Técnicos / Технические данные

spessore thickness épaisseur espesor Толщина			pressione esercizio working pressure pression d'exercice presión de trabajo Рабочее давление		packaging			
mm	mil	mm	bar	bar max	m	m	m	m
16	5	0,125	0,7	0,9	3800	1900	-	-
16	6	0,150	0,7	0,9	3000	1500	200	100
16	7	0,175	0,7	1,0	2500	1250	200	100
16	8	0,200	0,7	1,0	2200	1100	200	100
16	10	0,250	0,7	1,2	1800	900	-	-
16	12	0,300	0,7	1,5	1500	-	-	-
16	15	0,375	0,7	1,5	1200	-	-	-

Lunghezza ala

Tape lengths / Longueurs de rampe / Longitud de ala / Длина ленты

portata flow rate débit caudal расход	efficienza efficiency efficacité eficacia эффективность	distanza tra i gocciolatori dripper spacing distance entre les orifices separacion entre goteros Расстояние между капельницами			
		10 cm	20 cm	30 cm	40 cm
0,6	85	150	230	300	360
1,0	85	100	156	200	238
1,5	85	85	124	154	183
2,0	85	63	95	117	135
0,6	90	126	189	240	290
1,0	90	90	135	171	200
1,5	90	70	100	130	150
2,0	90	52	78	100	110



Ø 22 mm



filtrazione richiesta

filtration required
filtrage recommandé
filtración requerida
требуемый уровень фильтрации

100 micron
150 mesh

Dati tecnici

Technical data / Donnes techniques / Datos Técnicos / Технические данные

spessore thickness épaisseur espesor Толщина			pressione esercizio working pressure pression d'exercice presión de trabajo Рабочее давление		packaging			
mm	mil	mm	bar	bar max	m	m	m	m
22	6	0,150	0,7	0,9	2200	1100	-	-
22	7	0,175	0,7	1,0	2000	1000	-	-
22	8	0,200	0,7	1,0	1700	-	-	-
22	10	0,250	0,7	1,2	1300	-	-	-

Lunghezza ala

Tape lengths / Longueurs de rampe / Longitud de ala / Длина ленты

portata flow rate débit caudal расход	efficienza efficiency efficacité eficacia эффективность	distanza tra i gocciolatori dripper spacing distance entre les orifices separacion entre goteros Расстояние между капельницами		
		20 cm	30 cm	40 cm
0,6	85	430	550	664
1,0	85	300	360	495
1,5	85	220	270	370
2,0	85	165	200	280
0,6	90	340	440	540
1,0	90	260	330	405
1,5	90	190	245	304
2,0	90	140	185	230

Details make the difference

Ampia gamma di portate, spaziature e spessori

Wide selection of flow rates, spacing and wall thicknesses

- ✓ Grand choix de débits, espacements et épaisseurs
- ✓ Amplia gama de caudales, espacios entre goteros y espesores
- ✓ Широкий ассортимент расходов, расстояний и толщин

Ottima uniformità di erogazione

Excellent water distribution

- ✓ Excellent uniformité de distribution
- ✓ Óptima uniformidad de suministro de agua
- ✓ Оптимальный равномерный расход

Elevata tolleranza all'occlusione

High clogging resistance

- ✓ Résistance au bouchage très élevée
- ✓ Alta resistencia a la obstrucción
- ✓ Высокая устойчивость к засорению

Labirinto ad ampia sezione

Large section labyrinth

Labyrinthe à section large

Laberinto de sección amplia

Лабиринт широкого сечения

