

General

- Ideal for trees and bushes.
- Can be easily connected with spaghetti hose  $\Phi 6$  or with LDPE  $\Phi 12$ - $\Phi 32$  for various irrigation patterns.
- The outlet of "NESTOS" dripper can be connected with spaghetti hose 4mm supported with spike 3-7mm or support spike 4mm in order to guide the droplet to the required position.
- Dismantable, removable cap for easy cleaning
- Cylindrical disk with meander formation offers high reliability, precision and efficiency, minimizing clogging problems.



Characteristics

Maximum working pressure 4,0 bar.  
Available in 2, 4, 6, 8, 16, 24 and 32 l/h.  
Minimum filtration 120mesh (125micron).  
Colour coded according to flow rate.  
2 l/h - black      16 l/h - purple  
4 l/h - green      24 l/h - blue  
6 l/h - red        32 l/h - grey  
8 l/h - brown  
For installation use punch 3mm.

Pressure Πίεση	Discharge - Παροχή													
	Black Μαύρο		Green Πράσινο		Red Κόκκινο		Brown Καφέ		Purple Μώβ		Blue Μπλε		Grey Γκρι	
Bar	lt/h	gpm	lt/h	gpm	lt/h	gpm	lt/h	gpm	lt/h	gpm	lt/h	gpm	lt/h	gpm
0,5	1,32	0,006	2,87	0,013	4,14	0,018	5,18	0,023	10,19	0,045	14,20	0,062	21,00	0,092
<b>1,0</b>	<b>2,00</b>	<b>0,009</b>	<b>4,09</b>	<b>0,018</b>	<b>6,07</b>	<b>0,027</b>	<b>7,71</b>	<b>0,034</b>	<b>16,01</b>	<b>0,070</b>	<b>23,80</b>	<b>0,105</b>	<b>31,20</b>	<b>0,137</b>
1,5	2,63	0,011	5,03	0,022	7,61	0,034	9,72	0,043	20,85	0,092	29,50	0,130	39,00	0,172
2,0	3,11	0,014	5,83	0,026	8,91	0,039	11,45	0,050	25,16	0,111	34,20	0,151	46,20	0,203
2,5	3,64	0,016	6,54	0,029	10,08	0,044	13,01	0,057	29,10	0,128	37,80	0,166	52,00	0,229
3,0	4,08	0,018	7,18	0,032	11,15	0,049	14,43	0,064	32,77	0,144	42,50	0,187	57,50	0,253
3,5	4,43	0,019	7,76	0,034	12,15	0,053	15,77	0,069	36,23	0,160	45,60	0,201	62,70	0,276
4,0	4,83	0,021	8,15	0,036	13,08	0,0575	16,45	0,072	39,62	0,174	49,10	0,216	66,00	0,291

